

Overview

HPE StoreEver LTO Ultrium Tape Drives

The family of HPE LTO Ultrium tape drives is the Hewlett Packard Enterprise premier line of backup and archive devices. Based on the LTO Ultrium format, an open standard with a well-defined twelve-generation roadmap, HPE LTO Ultrium tape drives offer customers the best choice for investment protection. With ultimate reliability and ease of use in mind, even at 100% duty cycles, the HPE rugged design builds on superior LTO technology and adds advanced features like hardware data encryption to create a new level of data protection. The tape drives employ dynamic data rate matching to adjust to the speed of the host, reducing wear and tear on both drive and media and increasing performance, even on slower hosts. The family of tape drives also features support for HPE Library and Tape Tools which provides diagnostics, and performance optimization. If data is critical to your business, protect it with an HPE LTO Ultrium tape drive.

HPE StoreEver LTO-9 Ultrium 45000 Tape Drive

The HPE LTO-9 Ultrium 45000 tape drive represents Hewlett Packard Enterprise's ninth generation of LTO tape drive technology capable of storing up to 45TB (compressed 2.5:1) per cartridge while providing ease of use with support for LTFS and AES 256-bit hardware data encryption easy-to-enable security to protect the most sensitive data and prevent unauthorized access of tape cartridges. Capable of data transfer rates up to 300 MB/sec (native), its Speed Matching feature further optimizes performance by matching speed of host to keep drives streaming and increase the reliability of the drive and media. HPE LTO Ultrium half-height drives are designed for server customers in direct attached storage (DAS) environments. The Ultrium 45000 tape drives provide investment protection with full read and write backward support with LTO-8 media. By increasing the capacity of the previous generation Ultrium drive by 50%, Hewlett Packard Enterprise customers now require fewer data cartridges to meet their storage needs, significantly reducing their IT costs and increasing their ROI.

HPE StoreEver LTO-8 Ultrium 30750 Tape Drive

The HPE LTO-8 Ultrium 30750 tape drive represents Hewlett Packard Enterprise's eighth-generation of LTO tape drive technology capable of storing up to 30TB (compressed 2.5:1) per cartridge while providing ease of use with support for LTFS and AES 256-bit hardware data encryption easy-to-enable security to protect the most sensitive data and prevent unauthorized access of tape cartridges. Capable of data transfer rates up to 300 MB/sec (native), its Speed Matching feature further optimizes performance by matching speed of host to keep drives streaming and increase the reliability of the drive and media. HPE LTO Ultrium half-height drives are designed for server customers in direct attached storage (DAS) environments. For IT organizations with stringent, long-term data retention requirements, the Ultrium 30750's WORM (Write-Once, Read-Many) data protection feature offers a simple and secure method for archiving records as part of a compliance solution to meet the toughest of industry regulations. The Ultrium 30750 tape drives provide investment protection with full read and write backward support with LTO-7 media. By doubling the native capacity of previous generation Ultrium drives, Hewlett Packard Enterprise customers now require fewer data cartridges to meet their storage needs, significantly reducing their IT costs and increasing their ROI.

Overview

HPE StoreEver LTO Ultrium Half-Height Tape Drives



HPE StoreEver LTO Ultrium External Tape Drive



HPE StoreEver LTO Ultrium Internal Tape Drive

Standard Features

HPE StoreEver LTO-7 Ultrium 15000 Tape Drive

The HPE LTO-7 Ultrium 15000 tape drive represents Hewlett Packard Enterprise's seventh-generation of LTO tape drive technology capable of storing up to 15TB (compressed 2.5:1) per cartridge while providing ease of use with support for LTFS and AES 256-bit hardware data encryption easy-to-enable security to protect the most sensitive data and prevent unauthorized access of tape cartridges. Capable of data transfer rates up to 300 MB/sec (native), its Speed Matching feature further optimizes performance by matching speed of host to keep drives streaming and increase the reliability of the drive and media. HPE LTO Ultrium half-height drives are designed for server customers in direct attached storage (DAS) environments. For IT organizations with stringent, long-term data retention requirements, the Ultrium 15000's WORM (Write-Once, Read-Many) data protection feature offers a simple and secure method for archiving records as part of a compliance solution to meet the toughest of industry regulations. The Ultrium 15000 tape drives provide investment protection with full read and write backward support with LTO-6 media, and the ability to read LTO-5 cartridges.

HPE StoreEver LTO-6 Ultrium 6250 Tape Drive

The HPE LTO-6 Ultrium 6250 tape drive represents HPE's sixth-generation of LTO tape drive technology capable of storing up to 6.25TB (compressed 2.5:1) per cartridge while providing ease of use with support for LTFS and AES 256-bit hardware data encryption easy-to-enable security to protect the most sensitive data and prevent unauthorized access of tape cartridges. Capable of data transfer rates up to 1.44TB/Hour (compressed 2.5:1), HPE's exclusive Data Rate Matching feature further optimizes performance by matching speed of host to keep drives streaming and increase the reliability of the drive and media. HPE LTO Ultrium half-height drives are designed for server customers in direct attached storage (DAS) environments. For IT organizations with stringent, long-term data retention requirements, the Ultrium 6250's WORM (Write-Once, Read-Many) data protection feature offers a simple and secure method for archiving records as part of a compliance solution to meet the toughest of industry regulations. The Ultrium 6250 tape drives provide investment protection with full read and write backward support with LTO-5 media, and the ability to read LTO-4 cartridges.

HPE StoreEver LTO-5 Ultrium 3000 Tape Drive

The HPE LTO-5 Ultrium 3000 represents Hewlett Packard Enterprise's fifth-generation of LTO tape drive technology capable of storing up to 3TB per cartridge while providing ease of use with support for LTFS and AES 256-bit hardware data encryption easy-to-enable security to protect the most sensitive data and prevent unauthorized access of tape cartridges. Capable of data transfer rates up to 1TB/Hour. HPE's exclusive Data Rate Matching feature further optimizes performance by matching speed of host to keep drives streaming and increase the reliability of the drive and media. HPE LTO Ultrium half-height drives are designed for server customers in direct attached storage (DAS) environments. For IT organizations with stringent, long-term data retention requirements, the Ultrium 3000's WORM (Write-Once, Read-Many) data protection feature offers a simple and secure method for archiving records as part of a compliance solution to meet the toughest of industry regulations. The Ultrium 3000 provides investment protection with full read and write backward support with LTO-4 media, and the ability to read LTO-3 cartridge.

LTO Ultrium Technology

Linear Tape-Open technology was developed by three leaders in the storage industry - Hewlett Packard Enterprise, IBM, and Quantum - who brought together their combined expertise in tape technology to develop an entirely new format based on the best of existing technologies. Because LTO Ultrium technology was a new format, it required no cumbersome support of legacy formats, so it could be designed without compromising on reliability or performance. The LTO Program, a consortium of the three technology provider companies, has developed a well-defined twelve-generation roadmap.

Ultrium LTO-5 and LTO-6 tape drive technologies from Hewlett Packard Enterprise use a linear format of 1280 tracks and 2176 tracks (respectively), writing sixteen tracks simultaneously. Ultrium LTO-7, LTO-8 and LTO-9 tape drives feature a breakthrough in recording technology by writing thirty-two tracks simultaneously on a linear format of 3584 tracks, 6656 tracks and 8,960 tracks respectively. The data is written in a serpentine pattern; the tape reverses direction after each set of tracks is written. This provides higher density recording, enabling customers to lower costs and increase efficiency by storing more data on a single tape in an industry standard format.



Standard Features

The LTO standard for backward compatibility up to generation seven is to write back one generation and read back two generations; therefore:

- First-generation LTO Ultrium drives (HPE Ultrium 230, HPE Ultrium 232) read and write LTO-1 media
- Second-generation LTO Ultrium drives (HPE Ultrium 460, HPE Ultrium 448) read and write LTO-1 and LTO-2 media.
- Third-generation LTO Ultrium drives (HPE Ultrium 920, Ultrium 960) read and write LTO-2 and LTO-3 media and also read LTO-1 media.
- Fourth-generation LTO Ultrium drives (Ultrium 1840, Ultrium 1760) read and write LTO-3 and LTO-4 media and also read LTO-2 media.
- Fifth-generation LTO Ultrium drives (Ultrium 3280, Ultrium 3000) read and write LTO-4 and LTO-5 media and also read LTO-3 media.
- Sixth-generation LTO Ultrium drives (Ultrium 6650, Ultrium 6250) read and write LTO-5 and LTO-6 media and also read LTO-4 media.
- Seventh-generation LTO Ultrium drives (Ultrium 15000) read and write LTO-6 and LTO-7 media and also read LTO-5 media

Eighth-generation LTO Ultrium drives (Ultrium 30750) read and write LTO-7, LTO-7 Type M and LTO-8 media

Ninth-generation LTO Ultrium drives (Ultrium 45000) read and write LTO-8 and LTO-9 media

As part of the LTO open standard, all HPE tape drives and media offer the same standards of compatibility with tape drives and media manufactured by other LTO vendors.

LTO data compression (LTO-DC) is an enhanced version of Advanced Lossless Data Compression (ALDC) hardware compression. Compression is automatically turned off if the compressed data would cause an overall expansion in data size, hence optimizing the available capacity on the media. Data compression is also turned off if data is found to be uncompressible; thus, allowing for better data scans. The system is used in all LTO Ultrium tape drives.

The decision about which tape technology you should buy next should be based on your future, not your past, investment. Choose the LTO Ultrium format when you need the following advantages:

- Maximum reliability, capacity and performance
- Compatibility with a broad range of operating systems and servers (e.g., a mixed system environment)
- A legacy-free technology that uses the best attributes from a wide range of tape technologies without any compromises for backward compatibility requirements
- A solid roadmap for future generations of the technology
- An open format available from multiple vendors
- Lowest media cost of any 'superdrive' tape technology

Hardware Based Encryption

Since LTO generation 4, HPE LTO Ultrium tape drives support hardware-based encryption to enable greater levels of security:

- AES 256-bit Encryption
 - Easy-to-enable encryption for a secure backup
 - Helps prevent unauthorized accessed of tape media if cartridges are lost or stolen
 - Eliminates the need to purchase and manage additional h/w
- No loss in performance of backup

Linear Tape File System (LTFS)

LTFS makes tape self-describing, file-based, and easy-to-use, it also provides users with the ability to use standard file operations on tape media for accessing, managing and sharing files with an interface that behaves just like a hard disk. In addition, LTFS provides the ability to share data across platforms, as you would with a USB drive or memory stick. Simply load a tape into the drive, mount it into the file system, and it becomes visible as a disk.

For more information, including user guide, downloads and compatibility, visit: <http://www.hpe.com/storage/ltfs>



Standard Features

HPE StoreOpen Software

HPE StoreOpen Software is a free software application that helps LTFS users to use and manage single tape drives, autoloaders and tape libraries

Available for Windows, Linux and Mac environments for LTO Ultrium Drives, it provides a native GUI with a familiar look and feel. It is installed automatically as part of the LTFS package and it completely removes the need for low-level terminal commands by guiding users through the full process of select, prepare and mount an LTFS cartridge.

For more information, including user guide, downloads and compatibility, visit: <http://www.hpe.com/storage/StoreOpen>

Data Rate Matching

Data Rate Matching combines sophisticated buffer management with the HPE exclusive Variable Tape Speed technology to allow the tape drive to match its transfer rate to the host speed dynamically and continuously across the wide range of transfer rates. This feature ensures that the tape drive continues to stream data regardless of the environment, and brings two big advantages:

- It optimizes backup performance, regardless of the speed of the host or the network
- It minimizes rewinding and repositioning of the tape, reducing wear and increasing reliability

WORM (Write-Once, Read-Many) Drive and Media Support

Critical to the success of data retention policies in highly regulated environments is the ability to store and manage data in an unalterable state. Following stringent guidelines set forth by regulatory agencies such as the SEC and HIPPA, IT organizations must now integrate new solutions and policies that can verify the integrity of stored data for periods that can extend well beyond seven years.

LTO tape drives feature the ability to archive and store data in a non-rewriteable format that meets the most stringent regulatory guidelines. Using a combination of integrated fail-safe features in the drive firmware, cartridge memory, and tape formatting, LTO Ultrium drives can archive large amounts of data for periods of up to 30 years in a secure, untampered state. Since all LTO tape drives include support for both rewritable and WORM media, IT organizations can now easily integrate a secure, long-term archiving solution into their current data protection strategy. As compared to other technologies that feature support for WORM storage, LTO tape drives offers the advantages of:

- A single drive to support all backup and archiving needs
- Two distinctive tape cartridges to easily distinguish and manage both rewriteable and WORM data cartridges
- A specially designed WORM data cartridge with multiple integrated fail-safe features to prevent accidental or intentional overwriting of data
- High-capacity, low-cost HPE WORM media that can store up to 45TB (LTO-9) of data on a single data cartridge
- Support from many backup and archiving software vendors, providing the most comprehensive and mainstream support in the industry
- The LTO open standard that offers greater choice and compatibility across all third to eighth generation Ultrium products

Notes:

- While all HPE tape drives support LTO Ultrium WORM media, some third-generation LTO Ultrium tape drives from other manufacturers may not include read and write support for LTO Ultrium WORM media. For non-HPE LTO-3 and LTO-4 tape drives, please check the manufacturers' specifications to ensure this support is provided if you are using your WORM media. If WORM support is not provided, the drive will eject the WORM tape cartridge immediately upon insertion into the tape drive.
- LTO-9 WORM media is now supported on HPE Ultrium LTO-9 Drives with the latest firmware.



Standard Features

HPE Ultrium Storage Media

Hewlett Packard Enterprise branded Linear Tape Open (LTO) Ultrium cartridges are designed, manufactured and tested to provide outstanding reliability for backing up, archiving and restoring your data. We continuously monitor the quality of our branded tapes using what we believe is the industry's most comprehensive and forensic specification for quality and reliability. Using real life conditions and both Hewlett Packard Enterprise and non-HPE drives, we supplement extensive in-process QA parametric testing with ongoing drive based scrutiny, to make sure performance is excellent for any combination of device duty cycle and environment.

Because Hewlett Packard Enterprise is a leading supplier of both LTO tape devices and media, we have the ability to re-create many different scenarios mirroring how customers use their cartridges. And many of the HPE protocols are either unique in nature or scale, such as the HPE 'Green Tape', and HPE 'Environmental Interchange' tests, or far surpass industry standards, for example, The HPE 'Locate/Rewind/Append' test. Since the beginning of 2016, almost 700 million meters of media have been pulled and over 40 million gigabytes of data have been written in the HPE demanding GTT protocol. All of these ongoing tests are intended to ensure HPE LTO Ultrium media is the most reliable you can find. Your best choice for ease of support and maximum dependability is to use HPE-branded Ultrium cartridges at all times.

LTO-9 Media Initialization

Media initialization has been implemented in LTO-9 technology to optimize data placement according to the characteristics of each LTO-9 cartridge. Each new LTO-9 cartridge requires this one-time initialization prior to starting read/write operations, this is only required for the first use of a new LTO-9 cartridge, subsequent loads do not require additional initialization. The initialization process varies in time depending on the environmental conditions of tape and drive. Most initializations will complete within an hour; however, in some cases it can take up to 2 hours.

For standalone drives, the "Ready" LED and the "Tape" LED on the front panel of the drive will flash together rapidly to indicate that the media initialization is taking place. This will continue until the cartridge is ready to use.

Notes: LTO-9 WORM media is now supported on HPE Ultrium LTO-9 Drives with the latest firmware.

Diagnostics

HPE LTO Ultrium tape drives and automation are supported by HPE Library and Tape Tools (LTT). This tool is intended to help in the installation and maintenance of HPE tape drives and devices, including:

- Verifies installation of the drive
- Test/verify the health of the drive and media
- Provides Hewlett Packard Enterprise support with detailed device information
- Multiple options for finding and upgrading new firmware
- Performance optimization and recommendations
- Included with each Ultrium tape drive and available via free download supporting all HPE tape products

Instructions and downloads of HPE Library and Tape Tools are available at:

<https://www.hpe.com/us/en/product-catalog/storage/storage-software/pip.hpe-library-and-tape-tools.406729.html>

Compatibility

Hewlett Packard Enterprise extensive compatibility testing program assures that your HPE LTO Ultrium tape drive works with leading servers, operating systems, and backup applications - and not just those sold by Hewlett Packard Enterprise. HPE LTO Ultrium tape drives work seamlessly on many platforms, making them especially suitable if you have a mixed system environment. For the latest list of servers, workstations, operating systems, and backup software that support HPE Ultrium tape drives, check the tape backup compatibility pages on our Web site at: **<http://www.hpe.com/storage/StoreEverSupportMatrix>**



Standard Features

Server Compatibility

HPE Ultrium tape drives are supported on the following classes of HPE systems:

- HPE ProLiant DL servers
- HPE ProLiant ML servers
- HPE Integrity servers
- HPE 9000 servers
- HPE Apollo
- HP Inc. workstations

HPE Ultrium tape drives are also supported on server platforms from third-party manufacturers including:

- Dell
- IBM
- Sun

For details of which tape drive models work with which systems, including third-party systems, visit:

<http://www.hpe.com/storage/StoreEverSupportMatrix> for the latest hardware compatibility information.

OS Support

Microsoft® Windows, HPE-UX, Tru64, Red Hat Linux, SUSE Linux, IBM-AIX, Sun Solaris and other operating systems.

Notes: Please visit: <http://www.hpe.com/storage/StoreEverSupportMatrix> for the latest compatibility information.

Backup Software Support

Supported with HPE Data Protector, ARCserve Backup, EMC NetWorker, EMC Retrospect, IBM Tivoli Storage Manager, Veritas NetBackup, Veritas Backup Exec, BakBone NetVault, Commvault Simpana, Tolis Group BRU, Archiware P5, Qstar Archive Manager and others.

Notes: Please visit: <http://www.hpe.com/storage/StoreEverSupportMatrix> for the latest compatibility information.

Cables and Termination

All cables required for a typical internal and external connection to Hewlett Packard Enterprise servers are provided with your tape drive. For non-Hewlett Packard Enterprise servers, please consult your manufacturers' server specifications to determine if the cable provided with your LTO Ultrium tape drive is appropriate for use with that server.

SAS-based HPE LTO Ultrium models ship with SAS cable which allows direct attach from embedded SAS controller.

Notes: Visit: <http://www.hpe.com/storage/StoreEverSupportMatrix> for the latest compatibility information.

Performance Tuning

Use HPE Library and Tape tools to assist in this area at: <http://www.hpe.com/storage/tapetools>

Device performance test - will run data to an LTO drive direct from memory to prove the drive is capable of high performance if the data supply rate is fast enough.

System performance test for backup will read data from your primary storage device e.g. EVA disk array, and tell you how fast the array can supply multiple streams of data

System performance test for restore, this tool generates data of a known size and compressibility for benchmarking purposes.



Service and Support

Warranty and Services Included with the Product

Hewlett Packard Enterprise provides a 3-year, next-day, product exchange, limited warranty for all the Ultrium Tape Drives, plus 9x5 phone support for the duration of the warranty.

For more information about Hewlett Packard Enterprise's Global Limited Warranty and Technical Support, visit:

<http://www.hpe.com/storage/warranty>

HPE Support Services: Packaged server and storage services for increased uptime, productivity and ROI

When you buy HPE server and storage products and solutions, it's also a good time to think about what levels of support you may need. Our portfolio of service options reduce deployment and management worries while helping you get the most out of your server and storage investments. We take a holistic approach to your environment, bridging servers, blades, storage, software and network infrastructures with our packaged HPE Support Services for servers and storage.

Protect your business beyond warranty

When it comes to robustness and reliability, standard computing equipment warranties have matured along with technology. Good news that can also create problems stemming from depending on standard warranties designed to only protect against product defects and some downtime causes. Using a standard approach to warranty uplifts, such as HPE Support Services, helps reduce downtime risks and provides operational consistency for mission-critical and standard business computing.

HPE Support Services: Upgrading or extending standard server and storage warranties cost effectively

HPE Support Services offer a standard reactive hardware and software support services suite sold separately. The portfolio also provides a combination of integrated proactive and reactive services, such as Tech Care Service and Tech Care Advanced. In addition with HPE Proactive Select, you can acquire the specific proactive constancy and technical services. HPE Proactive Select menu offers a broad set of service options that you can mix and match depending on your specific requirements. Proactive service options include offers for server, storage, network, SAN device, software, environment and education services.

HPE server and storage lifecycle support services offers a full spectrum of customer care—from technology support to complex migrations to complete managed services. HPE Factory Express provides customization, integration and deployment services for turnkey solutions. HPE Education Services offer flexible, comprehensive training on to help your IT staff get the most out of your server and storage investments. HPE Financial solutions extend innovative financing and cost-effective asset management programs—from purchase to equipment retirement. Learn more: <http://www.hpe.com/services/storage>

Notes: Support Services availability may vary by product and country.

HPE Support Services are sold by Hewlett Packard Enterprise and Hewlett Packard Enterprise Authorized Service Partners:

- Services for customers purchasing from Hewlett Packard Enterprise or an enterprise reseller are quoted using Hewlett Packard Enterprise order configuration tools.
 - Customers purchasing from a commercial reseller can find HPE Support Services at [http:// www.hpe.com/services/storage](http://www.hpe.com/services/storage)
-



Service and Support

Free up resources with Operational Services from HPE Pointnext Services

HPE delivers services for IT by using proven best practices as well as automation and methodologies that have been tested and refined by HPE experts and artificial intelligence through thousands of deployments globally. Choose from the recommended services for customers purchasing from Hewlett Packard Enterprise or an authorized reseller. Services are quoted using Hewlett Packard Enterprise order configuration tools.

HPE Pointnext Tech Care.

HPE Pointnext Tech Care is the new operational service experience for HPE products. Tech Care goes beyond traditional support by providing access to product specific experts, an AI driven digital experience, and general technical guidance to not only reduce risk but constantly search for ways to do things better. HPE Pointnext Tech Care has been reimaged from the ground up to support a customer-centric, AI driven, and digitally enabled customer experience to move your business forward. HPE Pointnext Tech Care is available in three response levels. Basic, which provides 9x5 business hour availability and a 2 hour response time. Essential which provides a 15 minute response time 24x7 for most enterprise level customers, and Critical which includes a 6 hour repair commitment where available and outage management response for severity 1 incidents.

For more information: <https://www.hpe.com/services/techcare>

HPE Pointnext Complete Care

HPE Pointnext Complete Care is a modular, edge-to-cloud IT environment service that provides a holistic approach to optimizing your entire IT environment and achieving agreed upon IT outcomes and business goals through a personalized and customer-centric experience. All delivered by an assigned team of HPE Pointnext Services experts. HPE Pointnext Complete Care provides:

- A complete coverage approach – edge to cloud
- An assigned HPE team
- Modular and fully personalized engagement
- Enhanced Incident Management experience with priority access
- Digitally enabled and AI Driven customer experience

For more information: <https://www.hpe.com/services/completecure>

For more information: <https://www.hpe.com/us/en/services/datacenter-hybrid-services.html>



Configuration Information

HPE LTO Ultrium Half-Height Tape Drives

Model Name/Kit Contents

Description

SKU

LTO-9 Ultrium 45000 tape drives

HPE StoreEver LTO-9 Ultrium 45000 Internal Tape Drive

BC040A

- HPE StoreEver LTO-9 Ultrium 45000 Internal Tape Drive
- HPE LTO-9 Ultrium 45 TB RW Data Cartridge
- SFF8087 Mini SAS 4i to SFF8087 Mini SAS 3i cable
- Documentation

Notes: OD1 will appear after this part number on your sales order if factory integration is indicated.

HPE StoreEver LTO-9 Ultrium 45000 Internal TAA-compliant Tape Drive

BC041A

- HPE StoreEver LTO-9 Ultrium 45000 TAA Internal Tape Drive
- HPE LTO-9 Ultrium 45 TB RW Data Cartridge
- SFF8087 Mini SAS 4i to SFF8087 Mini SAS 3i cable
- Documentation

Notes: OD1 will appear after this part number on your sales order if factory integration is indicated.

HPE StoreEver LTO-9 Ultrium 45000 External Tape Drive

BC042A

- HPE StoreEver LTO-9 Ultrium 45000 External Tape Drive
- HPE LTO-9 Ultrium 45 TB RW Data Cartridge
- mini-SAS HD SFF8644 to mini-SAS HD SFF8644 cable
- Documentation

Notes:

- OD1 will appear after this part number on your sales order if factory integration is indicated.
- For US-English Localization please select BC042A#ABA
- This product is TAA (Trade Agreements Act) compliant

LTO-8 Ultrium 30750 tape drives

HPE StoreEver LTO-8 Ultrium 30750 Internal Tape Drive

BC022A

- HPE StoreEver LTO-8 Ultrium 30750 Internal Tape Drive
- HPE LTO-8 Ultrium 30 TB RW Data Cartridge
- mini-SAS SFF8482 to SFF8087 cable
- Documentation

Notes: OD1 will appear after this part number on your sales order if factory integration is indicated.

HPE StoreEver LTO-8 Ultrium 30750 TAA-compliant SAS Internal Tape Drive

BC024A

- HPE StoreEver LTO-8 Ultrium 30750 Internal Tape Drive
- HPE LTO-8 Ultrium 30 TB RW Data Cartridge
- mini-SAS SFF8482 to SFF8087 cable
- Documentation

Notes: OD1 will appear after this part number on your sales order if factory integration is indicated.



Configuration Information

Description

SKU

HPE StoreEver LTO-8 Ultrium 30750 External Tape Drive

BC023A

- HPE StoreEver LTO-8 Ultrium 30750 External Tape Drive
- HPE LTO-8 Ultrium 30 TB RW Data Cartridge
- mini-SAS High Density SFF8644 to mini-SAS SFF8088 cable
- Documentation

Notes:

- OD1 will appear after this part number on your sales order if factory integration is indicated.
- For US-English Localization please select BC023A#ABA
- This product is TAA (Trade Agreements Act) compliant

LTO-7 Ultrium 15000 tape drives

HPE LTO-7 Ultrium 15000 Internal Tape Drive

BB873A

- HPE LTO-7 Ultrium 15 TB RW Data Cartridge
- mini-SAS SFF8482 to SFF8087 cable
- Documentation

Notes: OD1 will appear after this part number on your sales order if factory integration is indicated.

HPE StoreEver LTO-7 Ultrium 15000 TAA-compliant Internal Tape Drive

BB953A

- HPE StoreEver LTO-7 Ultrium 15000 Internal Tape Drive
- HPE LTO-7 Ultrium 15 TB RW Data Cartridge
- mini-SAS SFF8482 to SFF8087 cable
- Documentation

Notes: OD1 will appear after this part number on your sales order if factory integration is indicated.

HPE StoreEver LTO-7 Ultrium 15000 External Tape Drive

BB874A

- HPE StoreEver LTO-7 Ultrium 15000 External Tape Drive
- HPE LTO-7 Ultrium 15 TB RW Data Cartridge
- mini-SAS High Density SFF8644 to mini-SAS SFF8088 cable
- Documentation

Notes:

- OD1 will appear after this part number on your sales order if factory integration is indicated.
- For US-English Localization please select BB874A#ABA
- This product is TAA (Trade Agreements Act) compliant

LTO-6 Ultrium 6250 tape drives

HPE LTO-6 Ultrium 6250 Internal Tape Drive

EH969A

- HP LTO-6 Ultrium 6.25 TB RW Data Cartridge
- Mini-SAS SFF8482 to SFF8087 cable Documentation

Notes:

- OD1 will appear after this part number on your sales order if factory integration is indicated.
- This product is TAA (Trade Agreements Act) compliant

HPE StoreEver LTO-6 Ultrium 6250 External Tape Drive

EH970A

- HPE LTO-6 Ultrium 6.25 TB RW Data Cartridge
- power cord
- mini-SAS High Density SFF8644 to mini-SAS SFF8088 cable
- Documentation



Configuration Information

Notes:

- For US-English Localization please select EH970A#ABA
- This product is TAA (Trade Agreements Act) compliant

Description

SKU

LTO-5 Ultrium 3000 tape drives

HPE StoreEver LTO-5 Ultrium 3000 SAS Internal Tape Drive

EH957B

- HP LTO-5 Ultrium 3 TB RW Data Cartridge
- mini-SAS SFF8482 to SFF8087 cable
- Documentation

Notes:

- OD1 will appear after this part number on your sales order if factory integration is indicated.
- This product is TAA (Trade Agreements Act) compliant

HPE StoreEver LTO-5 Ultrium 3000 SAS External Tape Drive

EH958B

- HP LTO-5 Ultrium 3 TB RW Data Cartridge
- power cord
- mini-SAS High Density SFF8644 to mini-SAS SFF8088 cable
- Documentation

Notes:

- For US-English Localization please select EH958B#ABA
- This product is TAA (Trade Agreements Act) compliant

Host Bus Adapters, Controllers, and Accessories for ProLiant Servers

HPE Smart Array E208e-p SR Gen10 (8 External Lanes/No Cache) 12G SAS PCIe Plug-in Controller

804398-B21

Notes: Recommended SAS HBA for connecting External LTO Ultrium tape drives to Gen10 ProLiant servers.

HPE Smart Array E208i-p SR Gen10 (8 Internal Lanes/No Cache) 12G SAS PCIe Plug-in Controller

804394-B21

Notes: Recommended SAS HBA for connecting Internal LTO Ultrium tape drives to Gen10 ProLiant servers.

Microsemi Adaptec HBA 1100-8e

A1100-8E

Notes: Recommended SAS HBA for DL & ML Gen9 servers only. HPE does not provide official support for this adapter, however the configuration is supported.

Media

HPE LTO-5 Ultrium 3TB RW Data Cartridge

C7975A

Notes: Write and read support for LTO-5 Ultrium 3280 and Ultrium 3000.

HPE LTO-5 Ultrium 3TB WORM Data Cartridge

C7975W

Notes: This data cartridge only supports Write-Once Read-Many recording format for LTO-5 drives. Data recorded to this data cartridge cannot be overwritten.

HPE LTO-6 Ultrium 6.25TB RW Data Cartridge

C7976A

Notes: Write and read support for LTO-6 Ultrium 6650 and Ultrium 6250.

HPE LTO-6 Ultrium 6.25TB BaFe RW Data Cartridge

C7976B

Notes: Write and read support for LTO-6 Ultrium 6650 and Ultrium 6250.



Configuration Information

Description

SKU

HPE LTO-6 Ultrium 6.25TB WORM Data Cartridge	C7976W
Notes: This data cartridge only supports Write-Once Read-Many recording format for LTO-6 drives. Data recorded to this data cartridge cannot be overwritten.	
HPE LTO-6 Ultrium 6.25TB BaFe WORM Data Cartridge	C7976BW
Notes: This data cartridge only supports Write-Once Read-Many recording format for LTO-6 drives. Data recorded to this data cartridge cannot be overwritten.	
HPE LTO-7 Ultrium 15TB RW Data Cartridge	C7977A
Notes: Write and read support for LTO-7 Ultrium 15000.	
HPE LTO-7 Ultrium WORM Data Cartridge	C7977W
Notes: This data cartridge only supports Write-Once Read-Many recording format for LTO-7 drives. Data recorded to this data cartridge cannot be overwritten.	
HPE LTO-8 Ultrium 30TB RW Data Cartridge	Q2078A
Notes: Write and read support for LTO-8 Ultrium 30750.	
HPE LTO-8 Ultrium 30TB WORM Data Cartridge	Q2078W
Notes: This data cartridge only supports Write-Once Read-Many recording format for LTO-8 drives. Data recorded to this data cartridge cannot be overwritten.	
HPE LTO-9 Ultrium 45TB RW Data Cartridge	Q2079A
Notes: Write and read support for LTO-9 Ultrium 45000.	
HPE LTO-9 Ultrium 45TB WORM Data Cartridge	Q2079W
Notes: This data cartridge only supports Write-Once Read-Many recording format for LTO-9 drives. Data recorded to this data cartridge cannot be overwritten.	
HPE Ultrium Universal Cleaning Cartridge	C7978A

Rack-mount Options

HPE StoreEver 1U Generic Rack Mount Kit	BC029A
Notes:	
<ul style="list-style-type: none"> For racked servers. No drives included. Accommodates up to two internal SAS half-height drives (such as LTO-5 Ultrium 3000, LTO-6 Ultrium 6250, LTO-7 Ultrium 15000, LTO-8 Ultrium 30750 or LTO-9 Ultrium 45000). Please refer to the 1U Rack-mount Kit web page for further information 	

Cables and Adapters

HPE 12Gb Mini SAS High Density (SFF-8644) to LTO Drive 4m Cable for 1U Rack Mount Kit	P35174-B21
Notes: Use this cable to connect HPE LTO-9 SAS internal tape drives to Mini SAS HD (SFF-8644) connectors	
HPE StoreEver 4m Mini SAS HD (SFF-8644) LTO Drive Cable for 1U Rack Mount Kit	876805-B21
Notes: Use this cable to connect HPE LTO-5, 6, 7 and 8 SAS internal tape drives to Mini SAS HD (SFF-8644) connectors.	
HPE StoreEver 4m Mini SAS (SFF-8088) LTO Drive Cable for 1U Rack Mount Kit	876804-B21
Notes: Use this cable to connect HPE LTO-5, 6, 7 and 8 SAS internal tape drives to SAS (SFF-8088) connectors.	



Configuration Information

Description	SKU
HPE SAS Min-Min 1x-2M Cable Assembly Kit	AE470A
Notes: Use this cable to connect HPE SAS external tape devices to HPE SAS controllers with external Mini-SAS (SFF8088) connectors.	
HPE SAS Min-Min 1x-4m Cable Assembly Kit	AE465A
Notes: Use this cable to connect HPE SAS external tape devices to HPE SAS controllers with external Mini-SAS (SFF8088) connectors.	
HPE 2.0m External Mini SAS High Density to Mini SAS Cable	716191-B21
Notes: Use this cable to connect HPE SAS external LTO-5, LTO-6, LTO-7, LTO-8 tape devices to HPE SAS controllers with external Mini-SAS high density connectors as used by HPE E208e-p or H241 Host Bus Adapters.	
HPE External 2.0m (6ft) Mini-SAS HD 4x to Mini-SAS HD 4x Cable	716197-B21
Notes: Use this cable to connect HPE SAS external LTO-9 tape devices to HPE SAS controllers with external Mini-SAS high density connectors as used by HPE E208e-p or H241 Host Bus Adapters.	



Technical Specifications

Family Information

	LTO-5 Ultrium 3000	LTO-6 Ultrium 6250	LTO-7 Ultrium 15000	LTO-8 Ultrium 30750	LTO-9 Ultrium 45000
Dimensions					
Form Factor	5¼-inch half-height				
Physical (HxWxD)	1.6 x 5.7 x 8.1 in				
Internal	(4.1 x 14.5 x 20.6 cm)				
Physical (HxWxD)	3 x 8.8 x 11.7 in				
External	(7.7 x 22.3 x 29.5 cm)				
Shipping (HxWxD)	7.9 x 9.4 x 11.4 in				
Internal	(24 x 31 x 39 cm)				
Shipping (HxWxD)	9.4 x 12.2 x 15.4 in				
External	(24 x 31 x 39 cm)				
Weight					
Out of box	3.2 lb (1.45 kg)				
Internal					
Out of box	10.3 lb (4.65 kg)				
External					
Shipping	5.1 lb (2.3kg)				
Internal					
Shipping	11 lb (5 kg)				
External					
Capacity					
Native	1.5 TB	2.5 TB	6 TB	12 TB	18 TB
Compressed	3 TB	6.25 TB	15 TB	30 TB	45 TB
(assumes 2:1 data compression for LTO-4 and 5; 2.5:1 compression for LTO-6 and higher)					
Buffer Size	256 MB	512 MB	1024 MB	1024 MB	1024 MB



Technical Specifications

	LTO-5 Ultrium 3000	LTO-6 Ultrium 6250	LTO-7 Ultrium 15000	LTO-8 Ultrium 30750	LTO-9 Ultrium 45000
Performance					
Sustained transfer rate, native	140 MB/s	160 MB/s	300 MB/s	300 MB/s	300 MB/s
Sustained transfer rate, compressed (assumes 2:1 data compression for LTO-4 and 5; 2.5:1 compression for LTO-6 and higher)	280 MB/s	400 MB/s	-	-	-
Burst transfer rate	600 MB/s (with 6Gb/s SAS)				1200 MB/s (with 12Gb/s SAS)
Data rate matching range	47-140 MB/s (native)	54-160 MB/s (native)	100-300 MB/s (native)	100-300 MB/s (native)	100-300 MB/s (native)
Average locate time (BOT - MOT)	52 s typical for a 1.5 TB tape (native)	50 seconds typical for LTO 6 media	60 seconds for LTO 7 media	60 seconds for LTO-8 media	60 seconds for LTO-9 media
Average load time	>19s	24s	12s	15s	17s
Average unload time	19s	19s	17s	24s	28s – 275s
Rewind time from EOT	96s (1.5 TB tape)	98s (2.5TB tape)	114s (6TB tape)	114s	123s
Rewind tape speed	9.0 m/s				
Reliability					
MTBF	250,000 hours at 100% duty cycle				
Uncorrected Error Rate	1 in 1x10 ¹⁷ bits		1 in 1x10 ¹⁹ bits		
Media Compatibility					
	LTO Ultrium 3 (Read only); LTO Ultrium 4 (Read and Write); LTO Ultrium 5 (Read and Write)	LTO Ultrium 4 (Read only); LTO Ultrium 5 (Read and Write); LTO Ultrium 6 (Read and write)	LTO Ultrium 5 (Read only); LTO Ultrium 6 (Read and Write); LTO Ultrium 7 (Read and write)	LTO Ultrium 7 (Read and Write); LTO Ultrium 8 (Read and Write)	LTO Ultrium 8 (Read and Write); LTO Ultrium 9 (Read and Write)
Tape Format					
Recording method	16-channel linear serpentine		32-channel linear serpentine		
Recording format	LTO Ultrium 5 LTO Ultrium 4 (for 800 GB tape)	LTO Ultrium 6 LTO Ultrium 5 (for 1.5 TB tape)	LTO Ultrium 7 LTO Ultrium 6 (for 2.5 TB tape)	LTO Ultrium 8 LTO Ultrium 7 (for 6 TB tape)	LTO Ultrium 9 LTO Ultrium 8 (for 12 TB tape)
Data compression	LTO DC dual mode compression (an enhanced version of ALDC)				
Error detection/correction	Reed-Solomon				
Read channel technology	Partial Response Maximum Likelihood (PRML)				
Data encoding method	RLL 32/33				



Technical Specifications

	LTO-5 Ultrium 3000	LTO-6 Ultrium 6250	LTO-7 Ultrium 15000	LTO-8 Ultrium 30750	LTO-9 Ultrium 45000
Interface					
Interface type	6Gb/sec Dual Port SAS				12Gb/sec Dual Port SAS
SAS connector	SAS Internal: mini-SAS SFF8482 SAS External: mini-SAS SFF8088		SAS Internal: mini-SAS SFF8482 SAS External: mini-SAS SFF8088		SAS Internal: mini-SAS SFF8482 SAS External: mini-SAS HD SFF8644
Power Specifications					
Power requirements Internal (including rack-mount model)	5V@3.5A (typical) +5V@3.7A (max) +12V@0.7A (typical) +12V@1.9A (max)	5V@3.5A (typical) +5V@4.0A (max) +12V@0.6A (typical) +12V@2.5A (max)	5V@4.0A (typical) +5V@4.5A (max) +12V@1.0A (typical) +12V@3.5A (max)	5V@4.0A (typical) +5V@4.5A (max) +12V@1.2A (typical) +12V@4.0A (max)	5V@4.0A (typical) +5V@4.0A (max) +12V@1.2A (typical) +12V@3.5A (max)
Power requirements External	100 to 240 VAC, 50-60 Hz, auto-ranging, 0.7A max	100 to 240 VAC, 50-60 Hz, auto-ranging, 0.8A max	100 to 240 VAC, 50-60 Hz, auto-ranging, 0.8A max	100 to 240 VAC, 50-60 Hz, auto-ranging, 0.8A max	100 to 240 VAC, 50-60 Hz, auto-ranging, 0.8A max
Power consumption	7 Watts idle 24 Watts typical 34 Watts max	4.1 Watts idle 24.5 Watts typical 39 Watts max	11 Watts idle 31Watts typical	11 Watts idle 31Watts typical	17 Watts idle 33 Watts typical
Environmental Specifications					
Temperature range	50° F to 95° F (10° C to 35° C) if 4 CFM airflow is provided 50° F to 104° F (10° C to 40° C) if, 6 CFM airflow is provided		Recommended Operating: 59° F to 77° F (20° C to 25° C) if 3 CFM airflow is provided Allowable Operating: 59° F to 95° F (10° C to 40° C) if 3 CFM airflow is provided		Recommended Operating: 59° F to 77° F (15° C to 25° C) if 3 CFM airflow is provided Allowable Operating: 59° F to 95° F (15° C to 35° C) if 3 CFM airflow is provided
			Non-Operating: -40° F to 151° F (-40° C to 66° C, -40° C to 60° C for LTO-7)		-40° F to 140° F (-40° C to 60° C
Non-condensing humidity range	Operating: 20 to 80% RH (Non-condensing, max wet bulb temperature = 26C)				Recommended Operating: 20 to 50% Allowable Operating: 20 to 80% (Non-condensing, max wet bulb temperature = 22C)
	Non-Operating: 10 to 95% (90% for LTO-7)RH (Non-condensing, max wet bulb temperature = 26C)		Non-Operating: 10 to 95% (90% for LTO-8)RH (Non-condensing, max wet bulb temperature = 26C)		5 to 80% for LTO-9 (Non-condensing, max wet bulb temperature = 26C)

Technical Specifications

Standards Compliance

- CSA Certification to C22.2, No.60950 (cCSAus)
 - TÜV EN60950 (IEC 60950 and EN60950)
 - CE Declaration of Conformity
 - FCC 47 CFR Parts 15
 - NOM
 - VCCI
 - C-TICK
 - RRL
 - BSMI
 - GOSH
 - CB Certificate and Report (IEC 60950)
-

Front Panel LED Indicators

HPE LTO Ultrium 5, 6, 7,8 and 9 tape drives have five LED indicators on the front panel:

- Ready
- Drive
- Tape
- Clean
- Encryption

Please consult your HPE Ultrium Tape Drive "Getting Started Guide" for more information on how to use these LED indicators for ascertaining drive status and for help in troubleshooting your HPE LTO Ultrium tape drive.



Summary of Changes

Date	Version History	Action	Description of Change
07-Feb-2022	Version 43	Changed	Overview and Configuration Information sections were updated.
10-Jan-2022	Version 42	Changed	Changes made throughout the QuickSpecs
01-Nov-2021	Version 41	Changed	Service and Support section was updated.
17-May-2021	Version 40	Changed	Configuration Information section was updated.
06-Apr-2021	Version 39	Changed	Configuration Information section was updated.
07-Dec-2020	Version 38	Changed	Configuration Information section was updated.
05-Oct-2020	Version 37	Changed	Configuration Information section was updated.
08-Sep-2020	Version 36	Changed	Configuration Information section was updated.
17-Aug-2020	Version 35	Changed	QuickSpecs layout was updated and Branding Refresh was applied.
06-Apr-2020	Version 34	Changed	QuickSpecs layout was updated and Obso SKUs were removed
15-Apr-2019	Version 33	Changed	Overview, Product Highlights and Options sections were updated
04-Mar-2019	Version 32	Changed	Options section was updated.
02-Apr-2018	Version 31	Changed	Service and Support section and Options were revised.
05-Feb-2018	Version 30	Changed	Overview, Product Highlights, Compatibility, Options, and Technical Specifications were revised.
04-Dec-2017	Version 29	Changed	Overview, Product Highlights, Compatibility, Options, and Technical Specifications were revised.
04-Sep-2017	Version 28	Changed	Changes made throughout the QuickSpecs
07-Aug-2017	Version 27	Changed	Changes made throughout the QuickSpecs
11-Jul-2017	Version 26	Changed	Removed LTO-3 Ultrium 920 Tape Drives & Ultrium Full-Height Drives
11-Mar-2016	Version 25	Changed	Changes made to the options section
19-Feb-2016	Version 24	Changed	Changed a reference in the Option Section, Descriptions updated.
17-Dec-2015	Version 23	Changed	Changes made in the Overview and standard features sections
01-Dec-2015	Version 22	Changed	Changes made throughout the QuickSpecs
03-Apr-2015	Version 21	Changed	Remove OD1 for internal drives into rackmount kits, SKUs descriptions were updated.
07-Nov-2014	Version 20	Changed	Changes made throughout the QuickSpecs.
09-May-2014	Version 19	Removed	LTO-4 Ultrium 1840 Tape Drives were removed.
02-May-2014	Version 18	Changed	Recommended Support was revised and Optional HPE Support Services was removed.
07-Mar-2014	Version 17	Changed	Image correction.
21-Feb-2014	Version 16	Changed	Added images.
23-Dec-2013	Version 15	Changed	HPE StoreEver LTO-2 Ultrium 448 Tape Drives were removed Performance was revised for LTO-6 Ultrium 6650
13-Sep-2013	Version 14	Changed	Changes were made to the following sections: Product Highlights Service and Support Options Technical Specifications
21-Dec-2012	Version 13	Changed	Changes were made to the following sections: Options: updated part # COL98A in HPE LTO Ultrium Full Height Tape Drives Technical Specifications: updated Capacity section
04-Dec-2012	Version 12	Changed	Changes made throughout the QuickSpecs.
19-Oct-2012	Version 11	Changed	Change was made to URL in Service and Support, HPE Support, and Warranty Information section.
13-Aug-2012	Version 10	Changed	Changes were made in Overview, Features, Product Highlights, Compatibility and Options sections.
28-Oct-2011	Version 9	Added	HPE StoreOpen Standalone was added to Product Highlights.

Summary of Changes

23-Sep-2011	Version 8	Changed	Updated the following: Linear Tape File Systems (LTFS) updated URL
8-Jun-2011	Version 7	Removed	Removed StorageWorks throughout the document.
27-May-2011	Version 6	Removed	HPE StorageWorks Ultrium 232 Tape Drive was removed.
29-Apr-2011	Version 5	Changed	Updated the following: replaced "Go Connect" link with the "SPOCK" link throughout the entire document.
29-Oct-2010	Version 4	Removed	Tape Array 5300 and Redundant, hot-swap power supply and fan for Tape Array 5300 were removed from Rack-mount Options.
27-Sep-2010	Version 3	Changed	Key Features and Customer Benefits were moved into Features Software in the Box was changed to Included Software in Product Highlights Related was changed to Optional for the HPE Support Services that will enhance your HPE product experience descriptions and Customer Technical Training, HPE Service Awards and Additional Services Information were completely revised in Service and Support, HPE Support and Warranty Information Software was changed to Upgrade included software to Data Protector Express in Options Value was added to Customer Benefits HPE Data Protector Express Basic was added to Backup Software Support Part numbers were removed from Models
18-Jun-2010	Version 2	Changed	Changes made within the Media section of Options.
29-Mar-2010	Version 1	New	New QuickSpecs



Copyright

Make the right purchase decision.
Contact our presales specialists.



Chat



Email



Call



Get updates



**Hewlett Packard
Enterprise**

© Copyright 2022 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft and Windows NT are US registered trademarks of Microsoft Corporation. Intel is a US registered trademark of Intel Corporation.

For tape drives and media, 1 GB = 1 billion bytes. Actual formatted capacity is less.

c04123270 - 13572 - Worldwide - V43 - 07-February-2022