StorageTek LTO Ultrium Data Cartridges





KEY FEATURES

- Increased capacity. StorageTek LTO Ultrium data cartridges provide higher capacity, which means fewer cartridges to buy and maintain, fewer tape mounts, and improved overall automation efficiency.
- Data security. StorageTek LTO
 Ultrium data cartridges are
 compatible with StorageTek LTO
 tape drives, which offer device-level
 data encryption to ensure data
 privacy and reduce the risk of data
 loss.

The high capacity and durability of Oracle's StorageTek Linear Tape Open (LTO) Ultrium data cartridges help you economically meet ever-increasing data storage requirements. With native capacity of up to 6.0 TB, StorageTek LTO Ultrium data cartridges are ideal for use in your archiving and backup applications. StorageTek LTO Ultrium data cartridges have high data integrity and longevity, so data is securely retained over its archived life. Backup and restore activities are accelerated, because more data is processed in less time with fewer tape mounts and dismounts.

Advanced Technology

StorageTek LTO Ultrium data cartridges feature a wide range of innovative technology advancements, including

- Highly reliable metal particle (Ultrium 5, Ultrium 6) and barium ferrite (Ultrium 7) media, with improved long-term magnetic stability for archival applications
- Non-contact 16 KB cartridge memory, which enables storage of historical usage records, indexing, and high-speed data searches by the drive
- Hardware-based AES 256-bit encryption capability of StorageTek LTO tape drives offers a high level of security during data storage and when transporting sensitive information

Engage the Storage Experts

Oracle service professionals help you address storage challenges by delivering integrated services and solutions that optimize and manage storage performance over the life of your data. Oracle's recognized, world-class service and customer care give you confidence that your technology investment is protected and that your business will be responsive to change. Oracle's storage service professionals can help you gain and sustain measurable results with the reliability and flexibility that you require. In addition, you can make your storage solution decisions even stronger with one of the largest selections of high-performance tape media in the industry.



STORAGETEK LTO ULTRIUM DATA CARTRIDGE SPECIFICATIONS

Basic Specifications	StorageTek Ultrium 7 Data Cartridge	StorageTek Ultrium 6 Data Cartridge	StorageTek Ultrium 5 Data Cartridge	StorageTek Ultrium Universal Cleaning Cartridge
Capacity, native (uncompressed)	6.0 TB	2.5 TB	1.5 TB	N/A
Tape length	960 m	846 m	846 m	319 m
Number of tracks	3584	2176	1280	N/A
Tape width	12.65 mm	12.65 mm	12.65 mm	12.65 mm
Tape thickness	5.6 µm	6.4 µm	6.4 µm	8.9 µm
Expected Archival Tape Life	>30 years	>30 years	>30 years	N/A
Cartridge color	Purple	Black	Red	Black
Environmental	•			
Operating	+50°F to +113°F (+10°C to +45°C), 10% – 80% RH, +79°F (+26°C) wet bulb maximum			
Storage up to four weeks	+61°F to +95°F (+16°C to +35°C), 20% – 80% RH, +79°F (+26°C) wet bulb maximum			
Storage, archive	+61°F to +77°F (+16°C to +25°C), 20% – 50% RH, +79°F (+26°C) wet bulb maximum			
Shipping	-10°F to +120°F (-23°C to +49°C), 20% - 80% RH, +79°F (+26°C) wet bulb maximum			
Compatibility Matrix				
	Ultrium 7 Drive	Ultrium 6 Drive	Ultrium 5 Drive	Ultrium 4 Drive
Ultrium 7 Cartridge	Read/write at 6.0 TB	Not compatible	Not compatible	Not compatible
Ultrium 6 Cartridge	Read/write at 2.5 TB	Read/write at 2.5 TB	Not compatible	Not compatible
Ultrium 5 Cartridge	Read-only	Read/write at 1.5 TB	Read/write at 1.5 TB	Not compatible
Ultrium 4 Cartridge	Not compatible	Read-only	Read/write at 800 GB	Read/write at 800 GB



CONTACT US

For more information about StorageTek LTO Ultrium Tape Cartridges, visit oracle.com/goto/tape or call +1.800.ORACLE1 to speak to an Oracle representative.

CONNECT WITH US





facebook.com/oracle



twitter.com/oracle



oracle.com

Integrated Cloud Applications & Platform Services

Copyright © 2016, Oracle and/or its affiliates. All rights reserved. This document is provided for information purposes only, and the contents hereof are subject to change without notice. This document is not warranted to be error-free, nor subject to any other warranties or conditions, whether expressed orally or implied in law, including implied warranties and conditions of merchantability or fitness for a particular purpose. We specifically disclaim any liability with respect to this document, and no contractual obligations are formed either directly or indirectly by this document. This document may not be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without our prior written permission.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.0116

